



JD Pro Series

A flagship holographic screen, engineered for media facades

◀ 95% Ultra-High Transparency, Putting Content Center Stage

Fixed holographic design with ultra-slim bezels minimizes structural obstruction, achieving up to 95% visual transparency. When off, it blends seamlessly into the facade; when on, the screen disappears so content takes center stage.



◀ 5000 nits for Semi-Outdoor Facades, Clearly Visible in Direct Sunlight

Purpose-built for semi-outdoor facades, 5000 nits delivers crisp, stable images even under direct sunlight. With 16-bit grayscale and static driving, colors are rendered with precision, true to life day and night, on screen and in camera.



◀ Ultra-Light Cabinets from 6.6 kg/m², Easing Facade Load Demands


Ultra-lightweight construction brings cabinet weight down to as low as 6.6 kg/m², reducing load requirements on building facades. Ideal for light-load scenarios such as aging facades and glass curtain walls.




Ultra-Slim Side Profile

Free-Form Straight & Curved Tiling for Endless Creative Shapes


Custom curved design with seamless straight-to-curved tiling meets creative, unconventional shapes. Fixed and suspended mounting adapts to existing facade structures with no additional steelwork, integrating naturally into the architectural design.



Fixed Installation



Suspended Installation



Curved Configuration

Minimalist Structure, Flawless Large-Module Tiling, Effortless Installation & Maintenance

Optimized structure delivers higher flatness across large modules, with independent front maintenance for easy service, balancing aesthetics with effortless upkeep.



Convenient Front-Access Maintenance



Rapid Installation

Application




Building Facade



Mall Atrium Hoisting



Retail Window



Cultural Tourism & Exhibition Display

Product Parameters

	Parameter	JD3.9 Pro	JD6 Pro	JD10 Pro
Physical Parameters	LED Type	SMD2222	SMD2222	SMD2222
	Pixel Pitch(mm)	3.91	6.25	10.4
	Pixel Density(dot/m ²)	65536	25600	9216
	Cabinet Size(mm)	1000*1000/1000*500	1000*1000/1000*500	1000*1000/1000*500
	Cabinet Resolution	256*256/256*128	160*160/160*80	96*96/96*48
	Weight(KG)	7	6.85	6.6
	Cabinet Material	Aluminum profile	Aluminum profile	Aluminum profile
	Physical Transmittance	47	58	65
	Visual Transmittance	82	90	95
Optoelectronic Parameters	Brightness(nit)	5000	5000	5000
	Gray scale(bit)	16	16	16
	Viewing Angle	140/140	140/140	140/140
	Color Temperature(K)	3500-12000	3500-12000	3500-12000
	Scan Mode	Static	Static	Static
	Frame Frequency(Hz)	60	60	60
	Operating Voltage	100~240	100~240	100~240
	Power Consumption(Max/Avg)	720/240	700/235	740/240
	Heat Generated (Max./Avg.)	2457/819	2389/796	2526/842
Application Parameters	Service Life	≥100000 h	≥100000 h	≥100000 h
	IP Rating	IP30	IP30	IP30
	Operating Temperature	-20°~+50°	-20°~+50°	-20°~+50°
	Storage Temperature	-20°~+50°	-20°~+50°	-20°~+50°
	Maintenance Method	Front / Rear maintenance	Front / Rear maintenance	Front / Rear maintenance
	Installation Method	Fixed / Hanging	Fixed / Hanging	Fixed / Hanging

Absen Optoelectronic Co.,Ltd

18-20F Building 3A, Cloud Park, Bantian,
Longgang District Shenzhen, 518129, P.R.China
T: +86-755-89747399 E: absen@absen.com
F: +86-755-89747599 W: www.absen.com

Absen Inc.

7120 Lake Ellenor Drive, Orlando,
Florida 32809, USA
T: +1-407-203-8870 E: info@usabsen.com
F: +1-407-203-8873 W: www.usabsen.com

Absen GmbH

Hessenring 4c, 64546 Moerfelden-Walldorf (Frankfurt am Main),
Germany
T: +49 (0) 6105 718941-0 E: europe@absen.com
F: +49 (0) 6105 718941-29 W: www.absen-europe.com



Twitter: @LEDAbsen
Facebook: @LEDAbsen
LinkedIn: Absen
Instagram: absenled